Easy: 1-2 hours

Athearn® Ready To Roll® GP60B & GP60M

To add a SoundTraxx Tsunami2 Digital Sound Decoder to your non-sound GP60B or GP60M model (announced in March 2003), you'll want to install a TSU-PNP EMD decoder.



Since 2009, Athearn has provided the option of purchasing some of their models equipped with Tsunami sound. If you have a GP60B or a GP60M model without sound that you would like to upgrade, purchase SoundTraxx P.N. 885013. This board is designed to simply replace the factory PCB that supplies power to the locomotive. You can complete the installation in one to two hours with no modification required to the model!



The Sound Upgrade



SoundTraxx Sound Decoder SoundTraxx Speakers SoundTraxx Accessories Other Parts

TSU-PNP, P.N. 885013	\$109.95
16 x 35mm Oval Speaker, P.N. 810113	\$14.50
30-gauge Wire, Purple, P.N. 810144	\$4.95
0.75mm Sheet Styrene, Evergreen P.N. 9030	\$4.19

Total \$133.59 (MSRP)

Other Tools You Will Need

- 25-watt Soldering Iron
- Rosin Core Solder
- Wire Strippers
- Wire Cutters
- X-ACTO[®] Knife
- Metal Straight Edge
- Dial Calipers
- Miniature Screwdriver Set
- Aguarium Sealant/Silicone
- Liquid Plastic Cement (TENAX-7R™ or equivalent)
- Kapton Tape
- Small Pliers
- Masking Tape